



NW2020 Library Reader

Long a favorite in libraries and media centers nationwide, the NW2020 Library Reader brings a full range of features to high volume rollfilm applications. The 2020's manual film drive lets you scan in variable speeds. The lens-mounted focus control provides a consistent, precise, razor sharp image from corner to corner of each frame. And with the dual intensity lamp and adjustable condenser, you can fine tune maximum illumination and resolution for each of the four optional lenses.

1-800-558-2153
(262) 367-1360 Fax (262) 367-1362
www.eyecom.com

NW2020

Library Reader

The 2020's film transport mechanism is designed to minimize rollfilm scratching and also accept aperture cards. Standard floating glass flats easily accommodate film splices, while optional Automatic Opening Glass Flats open when film is moved forward or backward to virtually eliminate scratching.

Full 360° image rotation optically straightens images filmed at random angles to an easy-to-read position, upright position. All controls are conveniently placed within easy reach.

- Convenient, front access to the film transport mechanism greatly simplifies film loading. An operational schematic diagram of the mechanism is printed above the back of the screen for loading, advancing and unloading the film, positioning and focusing the image, controlling light intensity, and using the 360° image rotation.
- An easy-to-reach lever vertically aligns the film to the precise framing desired. The lever's ball-and-socket construction makes for smooth, easy operation.
- The expansive 23" wide x 23" high screen — the largest available on any library microfilm reader — is slanted up at a 15° angle for easier reading. Made of easy-to-clean formica, the screen can be replaced right in the field.

SPECIFICATIONS

Application:	16mm and 35mm rollfilm
Screen size:	23" W x 23" H (584mm x 584mm)
Projection:	Front
Construction:	High pressure laminate, aluminum and plastic
Color:	White and brown
Lens options:	Standard: 35mm (19X) Optional: 16mm (42X) 24mm (26X) Zoom lens (15-24X)
Electrical:	Standard: 120V AC, 60 Hz Optional: 240V AC, 50 Hz
Lamp:	85W, 13.8V DED
Controls:	Front-mounted Low/Off/High lamp switch Side-mounted manual film drive Lens-mounted focus control Hanging film alignment lever
Dimensions:	24-5/8"W x 25"D x 41-1/2" H (625mm x 635mm x 1054mm)
Weight:	152 lbs. (69 kg)
Certification:	UL/CSA(approval pending)
Warranty:	30 Day (except lamp and screen)
Options:	Automatic opening glass flats
Accessories:	Cleaning Kit, Dust Cover

A MEDIA INDEPENDENT DOCUMENT MANAGEMENT COMPANY



EYE COMMUNICATION SYSTEMS, INC.

455 Industrial Drive

Hartland, WI 53029 USA

(800)558-2153 262) 367-1360

Fax: (262)367-1362 www.eyecom.com

Your Eye Com Dealer is: